




CHECK VALVE

IN-LINE / HIGH PRESSURE

15301-100 SERIES

POPPET TYPE
FEMALE NPTF



DESCRIPTION


- AN IN-LINE STYLE, CHECK VALVE INTENDED FOR BLOCKING FLUID FLOW.

OPERATION

- FLOW FROM "1" TO "2" IS ALLOWED WITH A STANDARD CRACK PRESSURE OF 5 PSI.
- FLOW FROM "2" TO "1" IS BLOCKED WITH A SPRING BIAS TO ASSIST IN STATIC AND LOW LOAD CONDITIONS.

FEATURES

- LOW PRESSURE DROP.
- LOW INTERNAL LEAKAGE, 5 DPM.
- HIGH PRESSURE.
- STEEL BODY.
- HARDENED STEEL POPPET.
- NO INTERNAL PACKINGS.
- * SPECIAL CRACK PRESSURES AVAILABLE UPON REQUEST.



- SPECIFICATIONS -	
HYDRAULIC SYMBOL	
OPERATING PRESSURE	5000 PSI
TEMPERATURE RANGE	250°F TO -40°F
STANDARD CRACK PRESSURE	5 PSI *
ALL DIMENSIONS IN INCHES	

- ORDERING INFORMATION -	
ASSEMBLY NUMBER	15301-10X-XX
SERIES NUMBER	
THREAD SIZE	
CRACK PRESSURE (PSI) (IF NON-STANDARD)	

MODEL	PORT 1 / 2	FLOW CAPACITY	L	HEX.
15301-102	1/4-18 NPTF	5 GPM	2.40	0.750
15301-103	3/8-18 NPTF	10 GPM	2.75	0.875
15301-104	1/2-14 NPTF	20 GPM	3.50	1.125
15301-106	3/4-14 NPTF	40 GPM	4.00	1.375
15301-108	1-11 1/2 NPTF	50 GPM	4.78	1.625
15301-110	1 1/4-11 1/2 NPTF	60 GPM	4.90	2.000



Vonberg Valve, inc.
HYDRAULIC VALVE SPECIALISTS

3800 INDUSTRIAL AVE.
ROLLING MEADOWS, IL 60008-1085
PH: (847) 259-3800 FAX: (847) 259-3997